## 50 Amp 125 Volt Cable Sets and Bulk Cable

IP56 SUITABILITY (Boatside)

UL c UL US LISTED
Cable sets only.

Our 50A 125V cable set is packed with high performance details from end to end that make a real difference. Completely factory pre-wired with molded-on devices. Designed to coil easily and lay flat.



50A 125V

### 50A 125V Cable Sets and Twist-Lock® Devices

| Description | Catalog Number |
|---|---|
| Yellow 50 ft. (15.2m) vinyl jacketed shore power cable set. #6 AWG type STOW is completely factory pre-wired with molded-on devices. Connector end has threaded metallic sealing ring to make inlet/connector interface watertight. **IP54 suitability (boatside)**. | **HBL61CM53** |
| Same as HBL61CM53 except with two high intensity LEDs. | **HBL61CM53LED** |
| Same as HBL61CM53 except 25 ft. (7.6m) in length. | **HBL61CM43** |
| Same as HBL61CM43 except with two high intensity LEDs. | **HBL61CM43LED** |
| Three conductor, #6 AWG type STOW, yellow PVC jacketed portable cord with jute fillersfor added flexibility. Ideal for making cable sets, extension cords and adapters will not mark boat's deck. 250 ft. (75.2m) lengths only. | **YC306250** |
| Nickel plated brass plug has heat resistant interior and combination metal and rubber cord grip, provides superior strain relief capability. Cord grip range is .44–1.14 in. (11.1–29.0). **IP20 suitability.** | **HBL63CM61*** |
| Single receptacle has a heat-resistant base. **IP20 suitability.** | **HBL63CM70*** |

*Note: *UL Listed and CSA Certified.*
*See page CC-13 for features and benefits.*


**HBL61CM53**
**HBL61CM43**


**HBL61CM53LED**
**HBL61CM43LED**


**HBL63CM61**

### Boots and Weatherproof Plates

| Description | Catalog Number |
|---|---|
| Yellow Seal-Tite® cover for weatherproofing 50A plugs. **IP55 suitability.** | **HBL77CM16**** |
| White Seal-Tite cover for weatherproofing 50A plugs. **IP55 suitability.** | **HBL77CM16W**** |
| Yellow Valox® lift cover for weatherproofing 50A receptacles. Meets requirements of the most stringent of UL's three listing categories for weatherproof plates. Stainless steel screws and a neoprene gasket included. For mounting to FS/FD type weatherproof boxes. **IP44 suitability.** | **HBL77CM74WO** |
| Same as HBL77CM74WO except gray in color. **IP44 suitability.** | **HBL7774WO** |
| Stainless steel wall plate for 50A receptacle. | **SS750** |

*Note: **Not UL Listed or CSA Certified.*


**HBL63CM70**


**HBL77CM16**


**HBL77CM16W**


**HBL77CM74WO**


**HBL7774WO**


**SS750**

*Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.*

*Dimensions in Inches (mm)*