Molded Straight Adapters — Now CSA Compliant

Description	Catalog Number
Permits use of 20A 125V Twist-Lock® locking type plug with 15 or 20A 125V straight blade receptacle. **IP20 suitability.**	**HBL21CM28***
Permits use of 15A or 20A 125V straight blade plug with 20A 125V Twist-Lock locking type receptacle. **IP20 suitability.**	**HBL21CM29***
Permits use of 30A 125V Twist-Lock locking type plug with 15 or 20A 125V straight blade receptacle. **IP20 suitability.**	**HBL31CM28**
Permits use of 15A or 20A 125V straight blade plug with 30A 125V Twist-Lock locking type receptacle. **IP20 suitability.**	**HBL31CM29**
Permits use of 30A 125V cable set, HBL61CM08 with 15 or 20A 125V straight blade receptacle. Anchor locking screw on plug when screwed down resists pullout of the cable set. **IP55 suitability** (Connector).	**HBL61CM22**
Same as HBL61CM22, except white.	**HBL61CM22W**
Permits use of 50A 125V cable set, HBL61CM53 with 15 or 20A 125V straight blade receptacle. **IP55 suitability** (Connector).	**HBL61CM54**
Permits use of 30A 125V cable set, HBL61CM08 with 50A 125V Twist-Lock receptacle, HBL63CM70. **IP55 suitability** (Connector).	**HBL61CM55**
Permits use of 50A 125V cable set, HBL61CM53 with 30A 125V Twist-Lock receptacle, HBL26CM10. **IP55 suitability** (Connector).	**HBL61CM56**
Permits use of 30A 125V cable set, HBL61CM08 with 50A 125/250V Twist-Lock receptacle, HBL63CM69. **IP55 suitability** (Connector).	**HBL61CM71*****
Permits use of 50A 125V cable set, HBL61CM53 with 50A 125/250V Twist-Lock receptacle, HBL63CM69. **IP55 suitability** (Connector).	**HBL61CM72*****
Permits use of 15A 125V 3 wire straight blade plug with 15 or 20A 125V 2 wire straight blade receptacle. **IP55 suitability** (Connector).	**HBL5273L***
Permits a 100A 125/250V cable set to plug into a single 50A 125/250V outlet. **IP55 suitability** (Connector).	**HBL61CM100****
Permits use of 15A straight blade plug with 30A 125V Twist-Lock receptacle; with GFCI protection. **IP55 suitability** (Plug).	**HBL105GF****


HBL31CM28


HBL21CM29


HBL61CM22


HBL61CM56


HBL61CM100


HBL105GF

Molded Y Adapters — Now CSA Compliant

Description	Catalog Number
Permits use of two 30A 125V cable sets, HBL61CM08, with one 50A 125/250V receptacle, HBL63CM69. **IP55 suitability** (Connectors).	**HBL64CM54**
Permits use of two 50A 125V cables sets, HBL61CM53, with one 50A 125/250V receptacle, HBL63CM69. **IP55 suitability** (Connectors).	**HBL64CM55**
Permits use of two 30A 125V cable sets, HBL61CM08, with one 30A 125V receptacle, HBL26CM10. **IP55 suitability** (Connectors).	**HBL64CM56**
Permits use of two 30A 125V cable sets, HBL61CM08, with one 50A 125V receptacle, HBL63CM70. **IP55 suitability** (Connectors).	**HBL64CM57****

*Note: *UL Listed.*
***Not CSA Certified.*
****The male plug end (50A 125/250V) has a blade removed and the blade slot filled with epoxy. Omitting the blade ensures achieving 125V safely. Adapters do not provide overcurrent protection and do not provide GFCI protection except HBL105GF.*


HBL64CM54


HBL64CM55


HBL64CM56


HBL64CM57

Dimensions in Inches (mm)