Product Specification Sheet

Simrad NMEA0183 - NMEA2000 Converter 6 ft Micro-C to Bare Wire

SKU: SIM-000-15939-001 Manufacturer part: 000-15939-001

Compiled by Common Ground from the supplied, source-linked Simrad research. Not a manufacturer-issued datasheet. Specifications apply only to the stated model or component.

Function
Decodes NMEA 0183 and converts data to NMEA 2000, and vice versa; configurable from a compatible MFD or instrument display

Power
Powered by the NMEA 2000 network at 12 V DC via an NMEA 2000 Micro-C male connector

Electrical
Power supply 12 V DC; operating voltage 9–18 V DC; 2 LEN, 0.48 W (40 mA at 12 V); reverse-polarity protection

Environmental
Operating temperature " 15°C to +55°C; IP67

Data
Baud rates 4800 (default), 9600, 19200, 38400, 57600 and 115200

Weight
0.1 kg (0.2 lb)

Sources
https://cxjdfr.files.cmp.optimizely.com/download/assets/en-us-NMEA-0183-Interface_EN_IG_988-13008-002_w.pdf/a85d1f36045e11f0909fee541559b234

https://downloads.simrad-yachting.com/#000-15939-001

Electrical ratings and physical dimensions are not shipping-package measurements. Kit specifications may describe an included component, not the entire kit.