Product Specification Sheet

Simrad QS80 Quick Stick Remote

SKU: SIM-000-10184-001 Manufacturer part: 000-10184-001

Compiled by Common Ground from the supplied, source-linked Simrad research. Not a manufacturer-issued datasheet. Specifications apply only to the stated model or component.

Function
Quick Stick joystick provides non-follow-up hand steering; spring-loaded joystick turns rudder while held and downward pull returns rudder to centre; can toggle auto/manual steering.

Display
2-inch monochrome bounded transflective display; 128 x 64 resolution; official product page describes integrated 1.7-inch display (the legacy manual gives the technical display specification).

Viewing direction
6 o'clock.

Interface and cable
Factory-connected 6 m (19.7 ft) Micro-C drop cable; CAN/NMEA 2000. SimNet via optional SimNet-to-Micro-C cable.

Power/current
Powered via CAN bus or SimNet; off network current <20 mA (NMEA 2000 LEN 1), on at maximum illumination <110 mA (LEN 3).

Weight
0.4 kg (0.88 lb).

Environment
-25 to +55 C (-13 to +131 F); exposed front weather protection corresponding to IPX6; compass-safe distance 0.4 m.

Mounting/dimensions
Flush panel or optional bulkhead/desktop frame; shared FU80/NF80/QS80 mounting template controls cutout.

Sources
https://www.simrad-yachting.com/simrad/type/autopilots/autopilot-remote-controllers/qs80-simrad-quick-stick-lever/

Electrical ratings and physical dimensions are not shipping-package measurements. Kit specifications may describe an included component, not the entire kit.