Marine Isolation Transformers

15 kVA and 25 kVA Models

- Protects Sensitive Equipment on Board
- Virtually Eliminates Potential for In-Water Stray Current
- Can be wired per ABYC E-11 for either a Polarization or Isolation Transformer system
- See website for additional specifications, weights, and dimensions



Constant Clean Safe Power

Isolation Transformers

Description	Color	Catalog Number	
		60 Hz	50/60HZ
15 kVA isolation transformer.	White powder coated steel	**HBL50AITW**	**HBLINTL50AITW**
15 kVA isolation transformer.	#316 Stainless steel	**HBL50AITSS**	**HBLINTL50AITSS**
15 kVA isolation transformer with auto-boost.	#316 Stainless steel	**HBL50AITSSB**	**HBLINTL50AITSSB**
15 kVA isolation transformer with auto-boost, 120/240 input.	#316 Stainless steel	—	**HBLINTL50AITSSBN**
25 kVA isolation transformer.	White powder coated steel	**HBL100AITW**	—
25 kVA isolation transformer.	#316 Stainless steel	**HBL100AITSS**	—
25 kVA isolation transformer with auto-boost.	#316 Stainless steel	**HBL100AITSSB**	—

Recommended Seal-tite® Cord Connectors

- For input and output cables
- Straight connectors for 1 and 1-1/2 inch KOs

Cord Connectors

Description	NPT Hub Size	Cord Diameter Inches (mm)		Form Size	Cast Aluminum Catalog Number
Straight male connectors.	1	1.13"-1.25"	(28.6-31.7)	F5	**SHC1048***
	1-1/2	1.25"-1.38"	(31.7-34.9)	F5	**SHC1059**
	1-1/2	1.38"-1.50"	(34.9-38.1)	F6	**SHC1061**

*Note: *Cable jacket may have to be stripped to pass through connector body.*



Dimensions in Inches (mm)