Closure Caps

Cap assemblies provide watertight sealing to a disconnected male IEC Pin and Sleeve plug or inlet. Manufactured of the same tough non-metallic material as the watertight IEC Pin and Sleeve devices for corrosion and abuse resistance.

Description	Catalog Number
Fits all 16 and 20A, 3 wire plugs and inlets. Fits all 16 and 20A, 4 wire plugs and inlets. Fits all 16 and 20A, 5 wire plugs and inlets.	PC320 PC420 PC520
Fits all 30 and 32A, 3 and 4 wire plugs and inlets. Fits all 30 and 32A, 5 wire plugs and inlets.	PC3430 PC530
Fits all 60 and 63A plugs and inlets.	PC60
Fits all 100 and 125A plugs and inlets.	PC100


PC3430

Cover Assemblies

Replacement cover assemblies for use with watertight connector bodies and receptacles. Exact replacement cover assemblies required to maintain proper water ingress. They are not reverse compatible. Replacement covers are not interchangeable. Kit contains cover, arm assembly and installation tool.

Description	IP67 Catalog Number	IP69K/4X Catalog Number
Fits all 16 and 20A, 3 wire watertight female devices. Fits all 16 and 20A, 4 wire watertight female devices. Fits all 16 and 20A, 5 wire watertight female devices.	CA320 CA420 CA520	HBLCA320 HBLCA420 HBLCA520
Fits all 30 and 32A, 3 and 4 wire watertight female devices. Fits all 30 and 32A, 5 wire watertight female devices.	CA3430 CA530	HBLCA3430 HBLCA530
Fits all 60 and 63A watertight female devices.	CA60	HBLCA60
Fits all 100 and 125A watertight female devices.	CA100	HBLCA100


CA60


HBLCA60

Cord Clamp and Locking Ring

Replacement cord clamp and locking ring for use with IEC plugs, connectors and inlets.

Description	Cord Clamp and Locking Ring	Locking Ring Only
Fits all 16 and 20A, 3 wire plugs, connectors and inlets. Fits all 16 and 20A, 4 wire plugs, connectors and inlets. Fits all 16 and 20A, 5 wire plugs, connectors and inlets.	CC320 CC420 CC520†	LR320* LR420* LR520*
Fits all 30 and 32A, 3 and 4 wire plugs, connectors and inlets. Fits all 30 and 32A, 5 wire plugs, connectors and inlets.	CC3430 CC530†	LR3430* LR530*
Fits all 60 and 63A plugs, connectors and inlets.	CC60	LR60*
Fits all 100 and 125A plugs, connectors and inlets.	CC100	LR100*

*Note: *Locking Ring only for plugs and inlets.*
†Consult factory.


CC3430


LR3430

Liquidtight Adapters

Machined aluminum or non-metallic adapters are available to provide a means for attaching flexible liquidtight metal conduit to rear of a Hubbell Pin and Sleeve plug or connector. To install, remove cord grip and two gland cap screws. Use screws to attach adapter. Kellems® liquidtight conduit connectors are available to control arc of bend and to prevent conduit pull-out where vibration, motion or strain is present. These grips interface directly with Hubbell's liquidtight adapters and are available in a wide variety of NPT sizes and configurations. Consult your local code grounding requirements before using liquidtight adapters.

Rating of Hubbell Pin and Sleeve Device	Liquidtight Conduit Size	Liquidtight Adapters		Optional Kellems Liquidtight Conduit Grip
		Aluminum	Non-Metallic	
16 and 20 Amp 3 and 4 Wire.	1/2" NPT	SAA12	—	074093402
	3/4" NPT	SAA34	—	074093403
16 and 20 Amp 5 Wire and 30 and 32 Amp 3 and 4 Wire.	1/2" NPT	SAB12	—	074093402
	3/4" NPT	SAB34	—	074093403
	1" NPT	SAB100	—	074093404
30 and 32 Amp 5 Wire and 60 and 63 Amp (all).	1/2" NPT	SAC12	SAC12NM	074093402
	3/4" NPT	SAC34	SAC34NM	074093403
	1" NPT	SAC100	SAC100NM	074093404
	1-1/4" NPT	SAC125	—	074093405
100 and 125 Amp (all).	1-1/4" NPT	SAD125	—	074093405
	1-1/2" NPT	SAD150	—	074093406


SAB34


074093403

Dimensions in Inches (mm)